



## Product certificate

**ADRIFÖL Truck Gear LongLife 75W-80**

**0002-000217**

### Description

ADRIFÖL Truck Gear LongLife 75W-80 is a fully synthetic high-performance gear oil with a special additive and inhibition, which ensure a perfect function of the gearbox. ADRIFÖL Truck Gear LongLife 75W-80 was developed especially for the requirements of commercial vehicle manual transmissions and is excellently suitable for very high mechanical and thermal loads, even with the longest oil change intervals.

### Instructions for use

ADRIFÖL Truck Gear LongLife 75W-80 is a high-performance gear oil for the supply of synchronized commercial vehicle manual transmissions, especially if Volvo 97307 or Volvo 97305 oils are required (see recommendations in the manufacturer's instructions). The shifting comfort is increased significantly. Extreme oil change intervals according to manufacturer's instructions up to 500,000 km reduce maintenance costs and increase economic efficiency.

### Quality classification

#### Specification

- API GL-4
- MIL-L-2105

#### Approval:

- MAN 341 Typ Z4
- VOLVO 97307
- ZF TE-ML 01L, 02L, 16K

**ADRIFÖL Truck Gear LongLife 75W-80 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- MAN 341 Typ E3
- DAF
- VOLVO 97305
- EATON (Extended drain) / IVECO / RENAULT
- VOLVO 97318
- MAN 341 Typ V-R

### Properties

- High additive reserves for extended oil change intervals according to manufacturer's instructions
- Best wear protection and best transmission efficiency
- Fuel savings even in short-haul operation even at low outside temperatures
- A stable lubricant film even at high loads
- An extraordinarily good corrosion protection and good non-ferrous compatibility
- High oxidative resistance prevents oil thickening and deposits
- Ultimate shear stability, within application times according to SAE class 75W-80
- Very strong protection against rust, corrosion and foaming
- Excellent EP properties

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	9,400	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	156		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	855,0	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-42	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

