



Product certificate

ADRIFÖL Ultra 20W-50

0002-000314

Description

ADRIFÖL Ultra 20W-50 is an engine oil on mineral oil basis with selected additives for demanding petrol engines from 2001 and later, and 4-stroke motorbikes.

ADRIFÖL Ultra 20W-50 has excellent lubricating film adhesion and good shear stability, as well as outstanding cleaning capability and high resistance to ageing.

Instructions for use

ADRIFÖL Ultra 20W-50 is intended for the typical operation of petrol engines in current and earlier (from 2001 onwards) cars, sport utility vehicles, vans and light trucks during maintenance measures recommended by vehicle manufacturers. Oils that meet the API SL requirements can be used wherever the API service category SJ and earlier categories are recommended.

ADRIFÖL Ultra 20W-50 is also excellently suited as engine oil for motorbikes, when the specification SAE 20W-50 JASO MA/MA2 is required.

Quality classification

Specification

- API SL
- JASO MA2

ADRIFÖL Ultra 20W-50 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- High oxidation stability
- Excellent shear stability
- Very good detergent and dispersant characteristics
- Lubrication film remains stable even with heavy strain
- Very good viscosity-temperature behaviour
- High safety reserves, even under boundary lubrication conditions
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	19,080	MM ² /S	DIN ISO 51562-2
viscosity index	122		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	882,0	KG/M ³	DIN EN ISO 12185
Pour Point	-24	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

14.12.2018 13:11:01