



Product certificate

**ADRIFÖL Universal Performance
15W-40**

0002-000604

Description

ADRIFÖL Universal Performance 15W-40 is a high quality truck engine oil formulated with Low SAPS technology. It can be used in older and new engines.

ADRIFÖL Universal Performance 15W-40 improves engine performance, reliability and cleanliness. It reduces fuel consumption and wear by reducing friction.

Instructions for use

ADRIFÖL Universal Performance 15W-40 is ideally suited for Euro 6 engines with exhaust systems and Euro 3, 4, 5 engines if specified by the engine manufacturer.

Quality classification

Specification

- ACEA E7/E9
- API CJ-4/SN
- Global DHD-1
- JASO DH-2

ADRIFÖL Universal Performance 15W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Ford WSS-M2C171-F1
- Mack EO-O Premium Plus
- MAN M 3575
- MB 228.31/228.51
- Renault VI RLD-3
- Volvo VDS-4
- Caterpillar ECF-2/ECF-3
- Cummins CES 20081
- DDC 93K218
- Deutz DQC III-10 LA
- MTU Type 2.1

Properties

- Stable viscosity behavior
- Protection against siltation, coking and varnishing
- Excellent detergent and dispersing properties
- Very good wear and corrosion protection
- High oxidation stability and engine cleanliness

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	98,9	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,5	MM ² /S	DIN ISO 51562-2
viscosity index	151		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	865,0	KG/M ³	DIN EN ISO 12185
Pour Point	-30	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.