



Product certificate

ADRIFÖL Universal UHPD 10W-40

0002-000103

Description

Universal UHPD 10W-40 is a universal engine oil on a basis of selected base oils combined with the latest additives for all diesel engines with or without turbocharging in lorries, buses and machinery.

Universal UHPD 10W-40 was developed as a UHPD (Ultra High Performance Diesel) engine oil with specific requirements on the diesel particulate filter for LOW SAPS technology. Low sulphur, phosphorus and ash content.

Instructions for use

Universal UHPD 10W-40 is a high-performance engine oil suitable for year-round use. It was designed for the new exhaust emission guidelines including for vehicles with exhaust gas recirculation systems.

Universal UHPD 10W-40 is universally applicable in all diesel engines with and without turbocharging. Suitable for EURO I, II, III, IV, V and EURO VI engines.

Quality classification

Specification

- ACEA E6/E7/E9
- API CI-4
- JASO DH-2

Approval:

- Deutz DQC-IV-10 LA
- MB-Freigabe 228.51
- Lizensiert: API CI-4
- MTU Type 3.1
- Mack EO-N
- Renault VI RLD-2
- MAN M 3477
- VOLVO VDS-3

ADRIFÖL Universal UHPD 10W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Caterpillar ECF-2
- MB 226.9
- Cummins CES 20076/20077/20078
- Renault VI RXD/RGD
- DAF HP-2
- Scania Low Ash
- MAN M 3277/M 3271-1

Properties

- Excellent oxidation stability
- Very good high-temperature stability
- Excellent detergent and dispersant properties
- Efficiency due to low fuel consumption
- Excellent cold starting performance; a fast engine lubrication even at low temperatures
- Very good viscosity and temperature behavior
- Neutrality towards sealants
- High wear protection

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	98,0	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,6	MM²/S	DIN ISO 51562-2
viscosity index	154		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	860	KG/M³	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

19.12.2018 01:00:05