



Product certificate

ADRIFÖL ZHF RL (grün)

0002-000262

Description

ADRIFÖL ZHF RL (green) is a special hydraulic oil on the basis of synthetic and mineral oils with high-quality additives.

Thanks to its special formulation, the properties of ADRIFÖL ZHF RL (green) play a crucial role. It guarantees outstanding cold stability.

active damping and engine support, for hydrostatic drive of ventilators, alternators and air conditioning systems, for stability and traction systems (ABS/ASR/ASC), central locking, electro-hydraulic convertible top controls, hydraulic brake boosters and hydropneumatic suspension for VW, Audi, Seat, Skoda. It is particularly ideal for use in cold countries.

Instructions for use

ADRIFÖL ZHF RL (green) is designed for use from -40°C to +130°C and is therefore recommended for the latest developments on the automotive market.

Quality classification

Specification

- ISO 7308
- DIN 51524 Part 3

ADRIFÖL ZHF RL (grün) is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- CHF202
- MB 343.0, MB 344.0, MB 345.0
- Opel 1940 766
- VW G 004 000
- Citroen 9979 A1
- Land Rover Cold Climate PAS Fluid 14315 LRN2261
- SAAB 93160548
- VOLVO 30741424

Properties

- Reliable protection against corrosion
- Extremely low pour point
- Improved viscosity and friction behavior
- A very good wear protection
- An excellent thermal stability
- A good foaming behavior
- Neutral towards sealing agents
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	21,300	MM ² /S	DIN ISO 51562-2
viscosity index	300		DIN ISO 2909
appearance	GREEN		visually
density at 15°C	823,0	KG/M ³	DIN EN ISO 12185
Pour Point	-72	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.